



COSHH SAFETY DATA SHEET

CM LM SILICONE TRANS

January 2016

1. Product and company identification

Product name: CM LM SILICONE LOW MODULUS SILICONE SEALANT
Colour: Translucent
Use: Used for making joints, sealing and gluing.
(for further information, refer to the product technical data sheet).

Supplier: CM SEALANTS
Selby Road
London
E11 3LT

Telephone number: 020 8519 6358
Email: info@cmsealants.co.uk

2. Composition/information on ingredients

PREPARATION

Chemical nature: Polydimethylsiloxanes, amorphous silica,
inert fillers & crosslinker.

Components contributing to the hazard:
None

Components presenting hazards: Vinylsilane trimethoxy (CAS: 2768-02-7): <5% - EEC
Classification: Xn ; R20. EC No. : 220-449-8 (*)

Further information: During use, on contact with humidity in the air releases:
Methanol (CAS: 67-56-1): 3% (max) – EEC Classification:
T;R23/24/25-39/23/24/25. EC No. :200-659-6 (*)
1-Butanol (CAS : 71-36-3) : < 2% - EEC Classification:
Xn;R22-37/38-41-67 EC No. :200-751-6 (*)

3. Hazards identification

MOST IMPORTANT HAZARDS

Adverse human health effects: Slightly irritating to eyes, respiratory system and skin.

Environmental effects: Presents no particular risk to the environment, provided the disposal
requirements (see section 13) and national or local regulations are
complied with.

Physical and chemical hazards:

Fire or explosion: Combustible.

Classification/Specific hazards: According to EEC criteria, this product is not classified as a “hazardous
preparation”.

Further information: After drying, may stick to the skin.



COSHH SAFETY DATA SHEET

CM LM SILICONE TRANS

January 2016

4. First-aid measures

Inhalation	Quickly move the person away from the contaminated area. If the person feels unwell: Call a doctor immediately.
Skin contact	Wipe off as much as possible (using a clean, soft, absorbent material). Wash immediately with plenty of soap and water.
Eye contact	Immediately rinse with water for a prolonged period whilst keeping the eyes wide open. If irritation persists, consult an eye specialist.
Ingestion	Consult a doctor if necessary.

5. Fire-fighting measures

Extinguishing media Suitable	Carbon dioxide (CO ₂). Foam. Powders. Water spray.
Not suitable	None to our knowledge. If there is a fire close by, use suitable extinguishing agents.
Specific hazards	For further information, refer to section 10: "Stability and Reactivity"
Specific fire fighting methods	Cool down the containers/equipment exposed to heat with a water spray.
Protection of fire-fighters	Self-contained breathing apparatus.

6. Accidental release measures

Personal precautions	Avoid contact with skin and eyes. Do not breathe vapours. Protective equipment: For further information refer to section 8 "Exposure-controls/personal protection". Mechanically ventilate the spillage area.
Environmental precautions	This product does not present any particular risk for the environment.
Methods for cleaning up	
Recovery	Recover the product by scraping with a spatula or a similar instrument. Collect up the product and place it in a spare container: suitably labelled tightly closed
Neutralization	Absorb residues with: inert absorbent material.
Cleaning/Decontamination	Decontaminate and wash the floor with: an appropriate solvent. (cf.: § 9) Then wash with plenty of water.



COSHH SAFETY DATA SHEET

CM LM SILICONE TRANS

January 2016

Disposal	For disposal of residues refer to section 13 "Disposal considerations". Incinerate contaminated materials at an authorized installation.
----------	---

7. Handling and storage

HANDLING

Technical measures	Ventilation.
Measures	Do not exceed the occupational exposure limits (OEL).

STORAGE

Technical measures	Does not require any specific or particular technical measures.
--------------------	---

Storage conditions

Recommended

Keep:
only in the original container
the container tightly closed and dry.

Incompatible products	Refer to the detailed list of incompatible materials (section 10 "Stability /Reactivity").
-----------------------	--

Packaging

Polyethylene liner in a metal drum varnished with epikote.
Polyethylene cartridges (outer packaging – cardboard box).

Packaging materials

Recommended

Polyethylene.
Coated metals.

Further information

The product polymerises on contact with air.

8. Exposure controls/personal protection

Engineering measures	Ensure good ventilation of the workstation.
----------------------	---

Control parameters

Occupational exposure limits

Limits (France)

Methanol : VLE : 260 mg/m³ (200 ppm).
Methanol : VME: 1300 mg/m³ (1000 ppm).
1-Butanol : VLE : 150 mg/m³ (50 ppm).

Limits (USA/A.C.G.I.H.)

Methanol : TLV (TWA) = 262mg/m³ (200 ppm)
Methanol : TLV (STEL) = 328 mg/m³ (250 ppm)
1-Butanol : TLV (TWA) = 152 mg/m³ (50 ppm)
(maximum value).



COSHH SAFETY DATA SHEET

CM LM SILICONE TRANS

January 2016

Limits (UK)	Methanol: OES: 200 ppm (266 mg/m ³). (Long-term exposure limit – 8h TWA reference period). OES: 250 ppm (333 mg/m ³). (Short-term exposure limit – 15 minute reference period). Sk notation – can be absorbed through the skin 1-Betanol: OES: 50 ppm (154 mg/m ³). (Short-term exposure limit – 15 minute reference period).
Surveillance procedures	Personal monitoring.
Personal protective equipment	
Respiratory protection	In the event of insufficient ventilation: Respiratory protective device with a gas filter.
Hand protection	Protective gloves made of rubber.
Eye protection	Safety spectacles.
Collective emergency equipment	Safety shower Eye fountain.

9. Physical and chemical properties

APPEARANCE

Physical state	Thixotropic paste.
Colour	Translucent
Odour	Weak
pH	Not applicable.
Specific temperatures	
Flammability characteristics	
Flash point	117 C (Closed cup, according to method AFNOR T 60103).
Auto-ignition temperature	Not applicable.
Oxidizing properties	Non-oxidizing material according to EEC criteria.
Specific gravity	Approx. 1400 kg/m ³ at 25 C (*)
Solubility	
in water	Practically insoluble.
in organic solvents	Very slightly soluble in: alcohol (ethanol) Dispersible (partial solubilisation) in: acetone Aliphatic hydrocarbons aromatic hydrocarbons (toluene, xylene). chlorinated solvents.



COSHH SAFETY DATA SHEET

CM LM SILICONE TRANS

January 2016

10. Stability and reactivity.

Stability	Stable at room temperature provided it is not on contact with air. Vulcanises at room temperature on contact with moisture in the air.
Hazardous reactions	
Conditions to avoid	No dangerous reactions known under normal conditions of use. See technical data sheet.
Hazardous decomposition products	On contact with humidity, releases: Methanol (Quantity potentially released:<3% of the weight of the product). 1-Butanol (Quantity potentially released:<2% of the weight of the product). On combustion forms: (Carbon oxides (CO + CO ₂)). amorphous silica (Calcium oxide)

11. Toxicological information

Acute toxicity	Not classified as harmful if swallowed (by calculation according to the conventional method)
Local effects	Repeated or prolonged contact may cause slight irritation to the skin. May cause slight temporary irritation to ocular mucous membranes.
Sensitisation:	No information available.
Specific effects	
Mutagenicity	No information available.
Further information	At high concentrations, the vapours can be irritating to the respiratory system.

12. Ecological information

MOBILITY

Precipitation	Slightly soluble product, readily forms deposits.
Expected behaviour of the product	Ultimate destination of the product: SOIL and SEDIMENT.

BIODEGRADABILITY

Ultimate aerobic biodegradability	Not biodegradable.
-----------------------------------	--------------------

BIOACCUMULATION

Bioconcentration factor	Not bioaccumulable.
-------------------------	---------------------



COSHH SAFETY DATA SHEET

CM LM SILICONE TRANS

January 2016

13. Disposal considerations

WASTE FROM RESIDUES

Destruction/Disposal Dispose of at a licensed waste collection point.

CONTAMINATED PACKAGING

Decontamination/cleaning Separate the different packaging components and treat them separately:

Destruction/Disposal Incinerate plastic packaging at a licensed installation.

Entrust the uncontaminated packaging to a licensed waste contractor.

Following decontamination, re-use or recycle metal packaging.

Disposable containers:

Incinerate at a licensed installation.

NOTE: The users attention is drawn to the possible existence of local regulations regarding disposal.

14. Transport information

INTERNATIONAL REGULATIONS

Land

Rail/road (RID/ADR) NOT restricted.

Sea (IMO/IMDG) NOT restricted.

Air (ICAO-IATA) NOT restricted.

OTHER REGULATIONS

United Kingdom: Rail/road NOT restricted.

NOTE: The above regulatory prescriptions are those valid on the date of publication of this sheet.
Given the possible evolution of transport regulations for hazardous materials, it would be advisable to check their validity with your sales office.

15. Regulatory information

LABELLING

EEC regulations Mandatory labelling (self-classification) of hazardous preparations:

Not applicable.

Additional phrases Safety Data Sheet available on request for professional users. (*)

Further regulations

United Kingdom

Handle in accordance with relevant British legislation:

Control of Substances Hazardous to Health Regulations

Environmental Hygiene Guidance: EH/40 Occupational Exposure

Limits (revised annually).



COSHH SAFETY DATA SHEET

CM LM SILICONE TRANS

January 2016

NOTE: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the Safety Data Sheet. The users attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. Other information

Registration numbers	These polymers are not concerned by the EINECS inventory. The corresponding monomers are registered in the EINECS inventory. All the other constituents of this preparation are registered in the EINECS inventory. All the components of this preparation are registered in the TSCA inventory.
R Phrases of § 2 & 3	R 20: Harmful by inhalation. R 22: Harmful if swallowed. R 23/24/25: Toxic by inhalation, in contact with skin and if swallowed. R 37/38: Irritating to respiratory system and skin. R 39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R 41: Risk of serious damage to eyes. R 67: Vapours may cause drowsiness and dizziness.

* Update Subheadings and text which have been modified since the previous version are indicated with an asterisk (*)

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is base on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfil his obligations regarding the use of hazardous products. This information is not exhaustive. This does not exonerate the user from ensuring that legal obligation, other than those mentioned, relating to the use and storage of the product, do not exist. This is solely his responsibility.

CM Sealants
Selby Road
Leytonstone
London
E11 3LT

020 8519 6358
info@cmsealants.co.uk