

# Declaration of Performance

## CM Sealants Stoneseal – All Colours

1. Identification code: CM Sealants Stoneseal
2. Batch No.: see imprint on packaging
3. Intended use: One component silicone sealant, neutral curing; Sealant for non structural use: facade, type F ext-int CC (F25 LM), glazing, type G – CC (G25 LM), sanitary, type S (XS1)
4. Manufacturer: CM Sealants  
Kendon House , Selby Road,  
Leytonstone , London , E11 3LT
5. Authorised representative: Mr Gary Brooks
6. System of assessment and verification of constancy: 3 plus 3
7. Notified body: MPA Dortmund NB-No. 0432 performed initial type testing under system 3 and issued the test-report.
8. ETA: not relevant
9. Declared performance:

Pretreatment: procedure B; substrate: glass, aluminium, mortar M1; without primer

| Essential characteristics   | Performance | Harmonised technical specification |
|---|-------------|------------------------------------|
| Fire behaviour (EN 13501)   | class E     | EN 15651-1: 2012-12                |
| Dangerous substances (details see Material Safety Data Sheet)                           | assessed    |                                    |
| Resistance to flow (EN ISO 7390)  | ≤ 3 mm      |                                    |
| Loss of volume (EN ISO 10563)   | ≤ 10 %      |                                    |
| Adhesion/cohesion properties at 100% extension after immersion into water (EN ISO 8340) | no failure  | EN 15651-2: 2012-12                |
| Adhesion/cohesion properties after exposure to light (EN ISO 11431)                     | no failure  |                                    |
| Elastic recovery (EN ISO 7389)  | ≥ 70 %      | EN 15651-3: 2012-12                |
| Tensile properties at -30°C (EN ISO 8339)   | ≤ 0,9 MPa   |                                    |
| Tensile properties at 100% ext., at -30°C (EN ISO 8340)                                 | no failure  |                                    |
| Resistance to microorganism (ISO 846)   | 0 or 1      |                                    |

|  |            |  |
|--|------------|--|
| Durability (EN ISO 8339, EN ISO 10590) | no failure |  |
|--|------------|--|

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Gary Brooks , Managing Director  
CM Sealants Limited .